



- Elektrostatisch pulverbeschichtet
- Aluminium-Druckguss-Kühlkörper und Rahmen
- 90° vertikal schwenkbar, 330° horizontal drehbar
- 22°- 36° Optik-Linsen
- Polymer KIT Box
- 3-Phasen-Schienenadapter

- *Electrostatic powder coated*
- *Die-cast aluminium heat sink and frame*
- *Adjustability allows 90° rotation for the vertical axis and 330° tilting for the horizontal axis*
- *22°- 36° optical lens options*
- *Polymer kit box*
- *With 3-phase track adaptor*

Farbe: sw (04), weiß (03), RAL9006 (00)

Colour: Black, white, metallic grey



Standard Version				
LSP1421001	1x44W	LED Modul	Aktivkühlung air pump	1216 gr.
LSP1421002	1x44W	LED Modul	Aktivkühlung fan	1140 gr.
LSP1421003	1x32W	LED Modul		1130 gr.
LSP1421005	1x22W	LED Modul		1130 gr.

DALI DIMM Version				
LSP1421010	1x22W	LED Modul	Aktivkühlung air pump	1140 gr.
LSP1421011	1x32W	LED Modul	Aktivkühlung fan	1140 gr.
LSP1421012	1x44W	LED Modul		1226 gr.
LSP1421013	1x44W	LED Modul		1150 gr.

LED-Daten und Lichtkurveninformationen / LED datas and Light curves information: Seite/Page 71

